


TECH SPEC SHEET

Offset Model

www.proflowpavers.com



Features - Summary Description

The spacing distributes the load and stresses more evenly across the entire paver surface. This helps enhance the structural integrity of the paved area

Physical Specification

Dry Weight Lbs	4.85
Dimensions In	2 7/16" x 2 7/16" x 2 2/5"
Block Count	14
Total Coverage Sqft	1
Physical Dimension Sqft	7/10

Installation Specifications

Pavers per Sqft	13.22
Gap Space In	2/5
Void Space Ft3	0.55
Romex Filler Lbs	2 1/4
Total Pavers Per Pallet	144
Pallet Weight Lbs	992
Pallet Dimensions In (W x L x H)	48 x 40 x 40

Material Specification (Wood)

COMMON NAME		BLACK LOCUST	
Color	Pale yellow to dark brown	Modulus of Elasticity	14,14 GPa
Scientific Name	Robinia Pseudoacacia	Maximum Crushing Strength	70.3 MPa
Grain	Tight Grain	Janka Hardness	7560 N
Density @ 12% Moisture	.66	Modulus of Rupture	133.8 MPa
Free Of Heart Center			

Environmental Benefits

Carbon Sequestered Per Paver 997.76 g Carbon



BIOFILTRATION



STORMWATER MANAGEMENT



HEAT ISLAND EFFECT



CHEMICAL FREE

Product Benefits



WARRANTY



PET FRIENDLY



ROT RESISTANT




FROST RESISTANT



PERMEABILITY

Offset Model



Features - Summary Description

The spacing distributes the load and stresses more evenly across the entire paver surface. This helps enhance the structural integrity of the paved area

Physical Specification

Dry Weight KG	2.2
Dimensions Cm	6.2 x 6.2 x 6
Block Count	14
Total Coverage Cm2	29
Physical Dimension Cm	27

Installation Specifications

Pavers per Sq Meter	13.22
Gap Space Cm	01
Void Space M3	0.015651
Romex Filler Grams	1000
Total Pavers Per Pallet	288
Pallet Weight KG	450
Pallet Dimensions cm (W x L x H)	90 x 120 x 94

Material Specification (Wood)

COMMON NAME		BLACK LOCUST	
Color	Pale yellow to dark brown	Modulus of Elasticity	14,14 GPa
Scientific Name	Robinia Pseudoacacia	Maximum Crushing Strength	70.3 MPa
Grain	Tight Grain	Janka Hardness	7560 N
Density @ 12% Moisture	.66	Modulus of Rupture	133.8 MPa
Free Of Heart Center			

Environmental Benefits

Carbon Sequestered Per Paver 997.76 g Carbon



BIOFILTRATION



STORMWATER MANAGEMENT



HEAT ISLAND EFFECT



CHEMICAL FREE

Product Benefits



WARRANTY



PET FRIENDLY



ROT RESISTANT



FROST RESISTANT




PERMEABILITY

TECH SPEC SHEET

Offset Model (half size)

www.proflowpavers.com



Features - Summary Description

The spacing distributes the load and stresses more evenly across the entire paver surface. This helps enhance the structural integrity of the paved area

Physical Specification

Dry Weight Lbs	1 2/5
Dimensions In	2 7/16"x 2 7/16" x 1 1/5"
Block Count	14
Total Coverage Sqft	1
Physical Dimension Sqft	3/4

Installation Specifications

Pavers per Sqft	1
Gap Space In	2/5
Void Space Ft3	1/4
Romex Filler Lbs	2 1/5
Total Pavers Per Pallet	288
Pallet Weight Lbs	992
Pallet Dimensions In (W x L x H)	48 x 40 x 40

Material Specification (Wood)

COMMON NAME		BLACK LOCUST	
Color	Pale yellow to dark brown	Modulus of Elasticity	14,14 GPa
Scientific Name	Robinia Pseudoacacia	Maximum Crushing Strength	70.3 MPa
Grain	Tight Grain	Janka Hardness	7560 N
Density @ 12% Moisture	.66	Modulus of Rupture	133.8 MPa
Free Of Heart Center			

Environmental Benefits

Carbon Sequestered Per Paver 628.57 g Carbon



BIOFILTRATION



STORMWATER MANAGEMENT



HEAT ISLAND EFFECT



CHEMICAL FREE

Product Benefits



WARRANTY



PET FRIENDLY



ROT RESISTANT



FROST RESISTANT




PERMEABILITY

TECH SPEC SHEET

Offset Model (half size)

www.proflowpavers.com



Features - Summary Description

The spacing distributes the load and stresses more evenly across the entire paver surface. This helps enhance the structural integrity of the paved area

Physical Specification

Dry Weight KG	1.4
Dimensions Cm	6.2 x 6.2 x 3
Block Count	14
Total Coverage Cm2	29
Physical Dimension Cm	27

Installation Specifications

Pavers per Sq Meter	13.22
Gap Space Cm	01
Void Space M3	0.0078255
Romex Filler Grams	1000
Total Pavers Per Pallet	288
Pallet Weight KG	450
Pallet Dimensions cm (W x L x H)	90 x 120 x 94

Material Specification (Wood)

COMMON NAME		BLACK LOCUST	
Color	Pale yellow to dark brown	Modulus of Elasticity	14,14 GPa
Scientific Name	Robinia Pseudoacacia	Maximum Crushing Strength	70.3 MPa
Grain	Tight Grain	Janka Hardness	7560 N
Density @ 12% Moisture	.66	Modulus of Rupture	133.8 MPa
Free Of Heart Center			

Environmental Benefits

Carbon Sequestered Per Paver 628.57 g Carbon



BIOFILTRATION



STORMWATER MANAGEMENT



HEAT ISLAND EFFECT



CHEMICAL FREE

Product Benefits



WARRANTY



PET FRIENDLY



ROT RESISTANT



FROST RESISTANT



PERMEABILITY